

Deep Sheen WB

water-borne, high-gloss protective treatment for pavers

DESCRIPTION AND USE

Paver Kare® Deep Sheen WB is the perfect treatment for concrete, clay or stone pavers, inside or out. This durable, water-borne protective treatment weather- and stain-proofs new or newly cleaned pavers, giving them a premium, vibrant gloss and shine. This water-borne treatment complies with all known AIM VOC regulations nationwide.

Deep Sheen WB's glossy finish guards pavers against etching and staining from acidic and alkaline contaminants, including food, drinks, cleaning chemicals and more. Fast-drying, non-blushing and non-yellowing, Deep Sheen WB is ideal for paver installations of any size – new or old.

ADVANTAGES

- Non-yellowing. Surface stays clear.
- Reduces clean up effort and resists construction stains.
- Acid and scratch resistant.
- Prevents efflorescence, dusting and spalling.
- Low odor, quick drying and re-coatable.
- Complies with all known national, state and district AIM VOC regulations.

Limitations

- Not suitable for use around pools, fountains or showers.
- Do not freeze.

TYPICAL TECHNICAL DATA

FORM: Milky white liquid, low odor
SPECIFIC GRAVITY: 1.03
pH: N/A
WT/GAL: 8.54 lbs.
ACTIVE CONTENT: 25%
TOTAL SOLIDS: 25% ASTM D 2369
FLASH POINT: >200°F (>93°C)
FREEZE POINT: 32°F (0°C)
SHELF LIFE: 1 year in tightly sealed, unopened container

VOC Information

USEPA: maximum VOC content 600 g/L
CARB SCM Districts: maximum VOC content 400 g/L
SCAQMD: maximum VOC content 100 g/L
Maricopa County, AZ: maximum VOC content 400 g/L
NEOTC: maximum VOC content 400 g/L

PREPARATION

Protect people, vehicles, property, plants, windows and all nonmasonry surfaces from product, splash, residue, fumes and wind drift. Protect and/or divert foot and auto traffic. Pavers must be clean, dry and in good repair before sealing with Deep Sheen WB.

Surface and Air Temperatures

Surface and air temperatures should be at least 50°F (10°C), and not above 90°F (32°C).

Equipment

Apply by brush, roller or sprayer. Do not atomize.

Storage and Handling

Store in a cool, dry place. Always seal container after dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed container in a dry place. Maintain temperatures of 45-100°F (7-38°C). Keep from freezing. Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

APPLICATION

Before use, read “Preparation” and “Safety Information.”

ALWAYS TEST for coverage and results before overall application. Test using the following application instructions. Let the test dry thoroughly before inspection.

Dilution

Do not dilute or alter. Stir thoroughly before application. Do not shake. Shaking may entrap air.

Application Instructions

Brush or roller

1. Saturate the entire surface. Avoid excessive overlapping.
2. Carefully brush out runs and drips.
3. Reapply, if needed, to produce an even appearance over the entire surface. Allow 30-40 minutes between applications, or until first coat is dry. Less material will be needed for the second coat.

Sprayer

1. Apply two or more thin, even coats to a total thickness of 2-4 mils wet. Let first coat dry 15 minutes or until it becomes tacky.
2. Apply two or more coats again, in the same manner, to produce an even appearance. Allow 30-40 minutes dry-time between each set of applications, or until first application is dry.

Coverage Rates and Drying Times

Expected coverage rates are:

Concrete	50-75 sq.ft./gal (5-7 sq.m./gal)
Clay	75-100 sq.ft./gal (7-9 sq.m./gal)
Stone	200-400 sq.ft./gal (19-37 sq.m./gal)

At 70°F (21°C) treated surfaces dry as follows:

To touch	30-40 minutes
Light foot traffic	4 hours
Normal traffic	overnight

Cleanup

Clean tools and equipment using soap and water.

SAFETY INFORMATION

Paver Kare® Deep Sheen WB is a water-borne, acrylic resin emulsion. Use appropriate safety equipment and job site controls during application and handling. Read full label and MSDS for precautionary instructions before use.

First Aid

Ingestion: Do not induce vomiting. Seek immediate medical assistance.

Eye Contact: Rinse eyes thoroughly for 15 minutes. Get medical assistance.

Skin Contact: Remove contaminated clothing and rinse thoroughly to remove residue. Get medical attention if irritation persists.

Inhalation: Remove to fresh air. Give artificial respiration if not breathing. Get immediate medical attention.

24-Hour Emergency Information: INFOTRAC at 800-535-5053

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care - technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com, and request the name of the Paver Kare® representative in your area.